

Magna™ CTX Range

Circulating oils

Description

Castrol Magna™ CTX circulating oil range are based upon high quality solvent-refined mineral oils and performance enhancing additives.

The Magna CTX range provides high oil film strength, outstanding rust protection, antiwear, antiscuff, anti-oxidation and water separating properties.

Application

Magna CTX circulating oils are engineered for use in MORGOIL back-up roll bearing systems such as those manufactured by Morgan Construction Company, Danieli, SMS Demag and others. These oils meet or exceed:

- Morgoil Lubricant Specification Rev. 1.1 (27 Jan 2005)
- Danieli Standard 0.000.001 Rev 14

Magna CTX 88 is also recommended for high speed No-Twist™ Rod Mills with a single lubricant circulating system. In No-Twist Rod Mills having two lubricating systems, the higher viscosity grades are used in the low speed roughing stands and the lighter grades in the higher speed finishing stands.

The higher viscosity grades of this product are also very suitable to be used as paper machine lubricants, due to the high thermal/oxidative stability, as well as the outstanding performance in rust protection, water separation and wear/scuffing protection. In such applications, it functions as a joint bearing/gear lubricant in most lubricating points, including the rolling bearings of the driers.

Magna CTX circulating oils are also suitable for use on other primary mill and mini-mill bearing application systems.

Advantages

- High viscosity indices.
- Excellent oxidation stability permits extended oil life.
- Exceptional hydrolytic stability in presence of moisture contamination.
- Excellent filterability in wet conditions.
- Excellent water separation properties.
- Good rust protection properties and low copper corrosion tendency.
- High film strength and outstanding anti-wear properties to provide high protection against bearing wear and gear scuffing under severe loading conditions.
- Low carbon forming tendency minimises bearing deposits and helps to maintain oil cleanliness under severe operating conditions.
- Efficient filtration with all types of filters, including those using fuller's earth as filtering medium.

Typical Characteristics

Name	Method	Units	CTX 88	CTX 150	CTX 220	CTX 320	CTX 460	CTX 680
ISO Viscosity Grade	-	-	100	150	220	320	460	680
Density @ 15°C / 59°F	ISO 12185/ASTM D4052	kg/m ³	888	890	898	903	900	900
Kinematic Viscosity @ 40°C / 104°F	ISO 3104/ASTM D445	mm ² /s	100	150	220	320	460	680
Kinematic Viscosity @ 100°C / 212°F	ISO 3104/ASTM D445	mm ² /s	11.3	14.6	19.2	24.6	31.2	38.6
Viscosity Index	ISO 2909/ASTM D2270	-	98	>95	>95	96	96	>90
Pour Point	ISO 3016/ASTM D97	°C/°F	-21/-6	-18/-0.4	-18/0	-15/5	-12/10	-9/16
Flash Point - open cup method	ISO 2592/ASTM D92	°C/°F	240/464	240/464	240/464	250/482	250/482	260/500
Flash Point - closed cup method	ISO 2719/ASTM D93	°C/°F	220/428	220/428	220/428	226/439	226/439	230/446
Foam Sequence I - tendency / stability	ISO 6247/ASTM D892	ml/ml	10/0	10/0	0/0	0/0	0/0	0/0
Foam Sequence II - tendency / stability	ISO 6247/ASTM D892	ml/ml	35/0	30/0	0/0	25/0	10/0	20/0
Foam Sequence III - tendency / stability	ISO 6247/ASTM D892	ml/ml	0/0	30/0	0/0	0/0	0/0	0/0
Water Separation @ 82°C / 180°F (40/37/3)	ISO 6614/ASTM D1401	min	10	10	10	10	15	15
Rust test - distilled water (24 hrs)	ISO 7120/ASTM D665A	Rating	Pass	Pass	Pass	Pass	Pass	Pass
Rust test - synthetic seawater (24 hrs)	ISO 7120/ASTM D665B	Rating	Pass	Pass	Pass	Pass	Pass	Pass
Copper corrosion (3 hrs@100°C/212°F)	ISO 2160/ASTM D130	Rating	1a	1a	1a	1a	1a	1a
Oxidation Stability - Rotating Pressure Vessel test	ASTM D2272/IP 229	min	330	348	311	286	261	-
Four Ball Weld Load test - Weld Point/ Load Wear Index	ASTM D2783	kgf	160/39.6	160/32.6	160/40.4	160/40.8	160/40.3	160/40.5
Four Ball Wear test - Wear Scar Diameter (15 or 40 kgf / 75°C / 1200 rpm / 1 hr)	ASTM D4172	mm	0.38	0.39	0.44	0.45	0.47	0.44
FZG Gear Scuffing test - A/8.3/90	ISO 14635-1	Failure Load Stage	>12	>12	>12	>12	>12	>12

Subject to usual manufacturing tolerances.

Magna™ CTX Range

27 Feb 2017

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Industrial, Technology Centre, Whitchurch Hill, Pangbourne, Reading, RG8 7QR, United Kingdom

<http://msdspds.castrol.com>