



## Techniclean D 890

Multi-metal ultrasonic dip process cleaner

### Description

Castrol Techniclean™ D 890 is an aqueous, mildly alkaline industrial cleaner containing corrosion inhibitors and a highly effective biodegradable surfactant package. The product is designed to be user-friendly and environmentally responsible. It is free of inorganic salts.

### Application

Techniclean D 890 is a low pH process cleaner for precision cleaning of all metals to the most demanding specifications in all types of dip and ultrasonic applications.

Techniclean D 890 is designed to remove a wide range of soils encountered in manufacturing, such as soluble oils, light-medium duty neat cutting or forming oils, lubrication oils, soft film corrosion preventives, swarf and general dirt.

### Conditions of Use

	Dip	Ultrasonic
Concentration Range	3 - 6%	2 - 5%
Temperature Range	up to 80°C / 176°F	50-70°C / 122- 158°F

Optimum conditions of use are depending on the detailed application requirements and the amount and nature of the soil being removed.

### Advantages

- Leaves a temporary corrosion preventive film on the metal surface – minimises scrap rate which improves productivity
- Highly effective biodegradable surfactant package – improves parts cleanliness and reduces re-work
- Free of inorganic salts, no rinsing required – enables process rationalisation
- Moderate pH-level – improves environment for the workforce
- Multi-metal compatible and suitable in hard and soft water – enables possible product consolidation

## Typical Characteristics

Description	Test Method	Unit	Value
Appearance	Visual	-	Clear-slightly hazy, yellow liquid
Density @ 15°C / 59°F	ASTM D1298	g/ml	1.06
pH (5% in DI-water)	ASTM E70/97	-	9.1
Cast Iron Corrosion Protection (5% in DI-water)	IP 287	-	Pass

## Concentration Control

1. Pipette 10 ml in an Erlenmeyer flask
2. Add 1 - 2 drops of indicator solution nitrazine yellow
3. Titrate with hydrochloric acid (c = 0,1 ml/l) until colour changes from blue to yellow
4. Concentration = required ml hydrochloric acid \* **factor 1,6**

## Storage

To avoid product deterioration always keep the container/drum tightly sealed. Store the product in a cool, dry place away from direct sunlight. Prevent exposure to frost and avoid water ingress. For optimum product stability, it is preferable to store the product indoors between 5°C and 45 °C / 41°F and 113°F.

For more details, please refer the product safety data sheet.

Techniclean D 890  
16 Dec 2014

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Industrial, Technology Centre , Whitchurch Hill , Pangbourne , Reading , RG8 7QR , United Kingdom

[www.castrol.com/industrial](http://www.castrol.com/industrial)