



Castrol Radicool Si-OAT

Engine Coolant and Antifreeze

Description

Castrol Radicool Si-OAT is a nitrite, amine and phosphate free antifreeze coolant with added silicate for the latest vehicles requiring silicate containing OAT technology. Aqueous solutions of Castrol Radicool Si-OAT act as both antifreeze and coolant and offer excellent corrosion protection to all metal parts found in the cooling systems of internal combustion engines.

Castrol Radicool Si-OAT should be used at concentrations of between 33% and 50% dilution with purified water to give optimum corrosion protection and freezing protection between -18°C and -36°C.

Application

Castrol Radicool Si-OAT has been developed to provide total protection for the metals used in the engine radiator systems, cylinder block heads, water pumps and heat exchangers.

In the majority of cases, coolants are not compatible and should not be mixed with other coolants unless directed by the equipment manufacturer. If using Castrol Radicool Si-OAT for the first time, ensure that the cooling system has been adequately flushed with clean water.

Advantages

Castrol Radicool Si-OAT protects for up to 3 years and has the following advantages

- Excellent low temperature protection
- Provides superior protection against all forms of corrosion
- Eliminates deposit formation , because of its phosphate free formulation
- Approved for use in Euro 6 trucks

Castrol Radicool Si-OAT is formally approved by MAN for use in those vehicles specifying MAN 324 Type Si -OAT coolants, including those vehicles built after Dec 2012.

Castrol Radicool Si-OAT is also suitable for use in older vehicles previously using MAN 324 Type NF and MAN 324 Type SNF fluids.

Castrol Radicool Si-OAT is approved for use in VW vehicles requiring VW TL-774G approval . It is also compatible with older VW TL774C (G11) and VW TL 774F (G12+) type fluids and can be used where VW TL 774J (G13) fluid is recommended.

Castrol Radicool Si-OAT is suitable for use in Mercedes Benz heavy duty vehicles manufactured after Oct 2011.

Typical Characteristics

Name	Method	Units	Castrol Radicool Si-OAT
Density @ 20C, Relative	DIN 51757	g/ml	1.123
Water	ASTM D1123	% wt	2.6
pH, Engine Coolants / Antirusts	ASTM D1287		8.5
Freezing point (50% vol dilution in water)	ASTM D1177	°C	-38.0
Appearance	Visual	-	Clear & bright

Product Performance Claims

ASTM D3306 (I)
ASTM D4985
BS6580:2010
JASO JIS K2234
MAN 324 Type Si-OAT
MB-Approval 325.5
VW TL- 774G

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol Radicool Si-OAT
02 Oct 2019
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com