

Product Data

Castrol llocut 154

High performance neat cutting oil

Description

Castrol llocut™ 154 is a chlorine and heavy metal free neat cutting oil.

Application

llocut 154 is designed for general machining of medium alloyed steel and non-ferrous metals.

	Cast Iron	Low-medium alloyed steel	High alloyed steel /nickel-chromium alloys	Titanium alloys	Aluminium alloys	Yellow metals
Honing/Superfinishing	1	-	ı	ı	-	-
Grinding	-	-	-		-	-
Drilling	-	-	-	-	-	-
Broaching/Gear manufacturing	-	-	-	-	-	-
General machining	1	1	-	-	1	1

Advantages

- Advanced additive technology gives high extreme pressure (EP) lubricity properties and lowering production costs through extended tool life
- Improved surface finish and increased cutting speeds leads to improvement of process efficiency
- Multi-metal compatibility using our superior additive technology provides opportunity for product consolidation
- Our chlorine and heavy metal free formulation improves the environmental profile and reduces disposal costs

Typical Characteristics

Properties	Standard	Unit	Data	
Appearance	Visual	Visual	Brown	
Viscosity @ 40°C	DIN 51562	mm²/s	35	
Viscosity@100°F	ASTM D 446	[SUS]	184	
Density @ 15°C	DIN 51757 ASTM D 1298	kg/m³	877	
	Calculated	lbs/gal	7.32	
Flashpoint COC	ISO 2592	"C	>190	
	ASTM D 92	" F	>370	
Copper corrosion	ISO 2160 ASTM D 130	3 hr at 100°C	1b	

	ester	active sulphur	inactive sulphur	phosphorous	calcium	chlorine	zinc
Additives	+	-	+	-	-	-	-

Castrol, Ilocut, and the Castrol logo are trademarks of Castrol Limited, used under licence

INTERNATIONAL All reasonable care has been taken to ensure that the information contained in this publication is accurate as of the date of printing. However, such information may, nevertheless, be affected by changes in the blend formulation occurring subsequent to the date of printing. Material Safety Data Sheets are available for all Castrol Ltd products. The MSDS must be consulted for appropriate information regarding storage, safe handling and disposal of a product.