

Castrol Ilocut 482

High performance neat cutting oil

Description

Castrol Ilocut™ 482 is a medium viscosity, chlorinated neat cutting oil.

Application

Ilocut 482 is designed for general machining, grinding and broaching of cast iron to high alloy steels and non-ferrous metals.

	Cast Iron	Low-medium alloyed steel	High alloyed steel/nickel-chromium alloys	Titanium alloys	Aluminium alloys	Yellow metals
Honing/Superfinishing	-	-	-	-	-	-
Grinding	✓	✓	✓	-	✓	✓
Drilling	-	-	✓	-	✓	✓
Broaching/Gear manufacturing	✓	✓	-	-	✓	✓
General machining	✓	✓	✓	-	✓	✓

Advantages

- Advanced additive technology gives high extreme pressure (EP) lubricity properties and lowers production costs through extended tool life
- Improved surface finish and increased cutting speeds leads to improvement of process efficiency
- Multi-metal machining using our superior additive technology provides opportunity for product consolidation

Typical Characteristics

Properties	Standard	Unit	Data
Appearance	Visual	Visual	Yellow
Viscosity @ 40°C	DIN 51562	mm ² /s	19
Viscosity@ 100°F	ASTM D 446	[SUS]	104
Density @ 15°C	DIN 51757 ASTM D 1298	kg/m ³	882
	Calculated	lbs/gal	7.36
Flashpoint	ISO 2592	°C	>180
	ASTM D 92	°F	>355
Copper corrosion	ISO 2160 ASTM D 130	3 h at 100°C	1b

	ester	active sulphur	inactive sulphur	phosphorous	calcium	chlorine	zinc
Additives	+	-	-	-	-	+	-

Castrol, Ilocut, and the Castrol logo are trademarks of Castrol Limited, used under licence

INTERNATIONAL. All reasonable care has been taken to ensure that the information contained in this publication is accurate as of the date of printing. However, such information may, nevertheless, be affected by changes in the blend formulation occurring subsequent to the date of printing. Material Safety Data Sheets are available for all Castrol Ltd products. The MSDS must be consulted for appropriate information regarding storage, safe handling and disposal of a product.

Castrol Limited, Pipers Way, Swindon, Wiltshire SN3 1RE, UK
www.castrol.com/industrial

Castrol Ilocut 482
 13 October 2008 Version 1