

Castrol Techniclean AS 105

Hydrocarbon solvent cleaner

Description

Castrol Techniclean™ AS 105 is a low odour, high flash point de-aromatised hydrocarbon solvent cleaner. It has excellent solvency power and is compatible with all metal substrates and most non-metal substrates.

Techniclean AS 105 is specifically recommended as an alternative to high volatile and chlorinated solvent cleaners.

Application

• Spray / Flood wash

Spray or flood wash application should be carried out in suitable low pressure cleaning equipment.

• Soak Tank

Components should be fully immersed in neat product. Contact time depends on soil severity.

• Ultrasonic Tank

Components should be fully immersed in neat product.

•Wipe Method

Product should be applied neat via hand held spray or brush and the surface is then wiped to a clean finish.

Advantages

- EC Solvent Directive (1999/13/EC): Solvent is not classified as a volatile organic compound (VOC) at 20°C (68°F)
- Excellent solvency power against animal, vegetable and mineral fats and oils and very low surface tension, allowing the fluid to penetrate into difficult to reach areas – improves parts cleanliness and reduces re-work
- Based on a high flash point solvent with a low aromatic content – improves environment for workforce
- No waste water is produced and solvent can be recycled by distillation – highly effective and yet economical

Typical Characteristics

	Test Method	Unit	Value
Appearance	Visual	-	clear, colourless liquid
Density @ 15°C	ISO 12185	kg/m ³	820
Density @ 59°C	ISO 12185	lb/gal	6.8
Initial boiling point	ISO 3405	°C (°F)	> 235 (> 455)
Flash Point PMCC	ASTM D 93	°C (°F)	> 101 (> 214)

User Advice

- May swell some rubber and plastics during long-term contact.
- Should not be used for cleaning live electrical equipment.
- The high flash point solvent supports compliance with the EC Solvent Directive (1999/13/EC). Please note, that its low volatility extends the drying time compared to conventional non-VOC compliant products.

Castrol, Techniclean (Lettered), and the Castrol logo are trademarks of Castrol Limited, used under licence

INTERNATIONAL All reasonable care has been taken to ensure that the information contained in this publication is accurate as of the date of printing. However, such information may, nevertheless, be affected by changes in the blend formulation occurring subsequent to the date of printing. Material Safety Data Sheets are available for all Castrol Ltd products. The MSDS must be consulted for appropriate information regarding storage, safe handling and disposal of a product.

Castrol Limited, Pipers Way, Swindon, Wiltshire SN3 1RE, UK
www.castrol.com/industrial