

Castrol Techniclean HP

High pressure spray process cleaner

Description

Castrol Techniclean™ HP is an aqueous, low alkalinity, industrial cleaner containing biodegradable surfactants and corrosion inhibitors.

Application

Techniclean HP is an inter-operational, multi-metal cleaner, suitable for cleaning parts and components in a wide range of industrial spray and intensive flood wash machines.

Techniclean HP is specifically developed for use in high-pressure process cleaning and deburring equipment.

Techniclean HP effectively removes soluble oils, light duty neat cutting or forming oils, lubrication oils, soft film corrosion preventives, swarf and general dirt.

Conditions of Use

| | |
|----------------------|----------------------------|
| Concentration Range. | 1 - 4% |
| Temperature Range: | Ambient - 65°C / 150°F |
| Spray Pressure | up to 1000 bar / 14500 psi |

Optimum conditions of use are depending on the detailed application requirements and the amount and nature of the soil being removed.

Advantages

- Effectively minimises excessive foam – reliable, reduces costly risk of dangerous cavitations/damage of high-pressure pumps
- Excellent demulsifying properties provide easy skimming and long bath life – reduces maintenance and disposal cost
- Leaves a temporary corrosion preventive film on the metal surface – minimises scrap rate which improves productivity
- Versatile; multi-metal compatibility and suitable in hard and soft water – enables possible product consolidation

Typical Characteristics

| | Test Method | Unit | Value |
|---------------------|-------------|-------------------|----------------------------|
| Appearance | Visual | - | Clear, light yellow liquid |
| Density @ 15°C | DIN 51 757 | kg/m ³ | 1040 |
| Density @ 59°F | DIN 51 757 | lb/gal | 8.7 |
| pH (5% in DI-water) | | - | 9.3 |

Concentration Control

- Pipette 10 ml in an Erlenmeyer flask
- Add 1 - 2 drops of indicator solution nitrazine yellow
- Titrate with hydrochloric acid (c = 0,1 ml/l) until colour changes from blue to yellow
- Concentration = required ml hydrochloric acid * **factor 1,0**

Castrol, Techniclean (Lettered), and the Castrol logo are trademarks of Castrol Limited, used under licence

INTERNATIONAL All reasonable care has been taken to ensure that the information contained in this publication is accurate as of the date of printing. However, such information may, nevertheless, be affected by changes in the blend formulation occurring subsequent to the date of printing. Material Safety Data Sheets are available for all Castrol Ltd products. The MSDS must be consulted for appropriate information regarding storage, safe handling and disposal of a product.

Castrol Limited, Pipers Way, Swindon, Wiltshire SN3 1RE, UK
www.castrol.com/industrial